EB-982W

Raise the bar with this bright and scalable, 4,200 lumens, WXGA projector, that offers multiple connectivity solutions and is simple to set up.

Optimise your presentation's potential with this bright WXGA projector that's capable of producing a large and scalable screen size. Excessive downtime is a thing of the past with this reliable projector that can deliver years of use before a replacement lamp is required or the air filter needs attention. It has a range of connectivity solutions and is fuss free to set up.

Excellent visibility for every presenter

With this WXGA projector, content will be bright, vivid and clear, ensuring that everyone can engage with the audience. Providing excellent visibility, this projector is scalable up to 280 inches and is bright even in high ambient lighting conditions. It's all thanks to the high 4,200-lumen output and 16,000:1 contrast ratio.

Minimal maintenance

Our reliable projectors and long-lasting lamps help to eliminate downtime and unnecessary service costs. Imagine what you could achieve with minimal interruptions - our projectors provide years of use before a replacement lamp is required.


Easy set up

Every working environment is different so you need a display solution that is simple to set up and position. With our wide 1.6x optical zoom and vertical/horizontal keystone correction, it's easy to get up and running quickly.

Utilise multiple devices

Capture your audiences' attention and nurture a collaborative environment with hassle-free connectivity solutions. With the iProjection App¹, it's easy to display content from PCs and smart devices. The split-screen function can be utilised to show content from multiple devices simultaneously, while the moderator function lets you review content before it is displayed.

DATASHEET / BROCHURE



KEY FEATURES

- 4,200lm and 16,000:1 contrast ratio vivid display
 3LCD technology and equally high White and Colour Light Output
- Minimal maintenance Years of uninterrupted use before maintenance is required
- Flexible installation Horizontal/vertical keystone correction and 1.6x optical zoom
- Enhanced connectivity Dual HDMI ports, RJ-45 Ethernet, optional wireless connectivity
- Collaborative features iProjection App¹, split-screen function, moderator function





PRODUCT SPECIFICATIONS

TECHNOLOGY Projection System	3LCD Technology, RGB liquid crystal shutter	WHAT'S IN THE BOX
LCD Panel	0,59 inch with MLA (D9)	• Main unit
IMAGE Color Light Output White Light Output Resolution	4.200 Lumen- 2.600 Lumen (economy) In accordance with IDMS15.4 4.200 Lumen - 2.600 Lumen (economy) In accordance with ISO 21118:2020 WXGA 2	 Remote control incl. batteries Warranty card Quick Start Guide
Native Contrast Lamp Keystone Correction	16.000 : 1 UHE, 230 W, 6.500 h durability, 17.000 h durability (economy mode) Auto vertical: ± 30 ° horizontal ± 30 °	Power cableHDMI Cable 1.8m
Colour Reproduction	Upto 1.07 billion colours	
OPTICAL		OPTIONAL ACCESSORIES
Throw Ratio Zoom Screen Size	1,38 - 2,24:1 Manual, Factor: 1 - 1,6 29 inches - 280 inches	 Soft Carry Case - ELPKS70 V12H001K70
Projection Distance Wide Projection Distance Tele Projection Lens F Number	0,9 m - 8,5 m 1,4 m - 13,7 m 1,51 - 1,99	 Lamp – ELPLP97 – EB9XX/W49/X/E20/U50/EB- x05/x41/x42/EH-TW6 V13H010L97
Projection Lens Focal Length	18,2 mm - 29,2 mm	• Air Filter - ELPAF54
Offset	10:1	V13H134A54
CONNECTIVITY USB Display Function Interfaces	2 in 1: Image/ Sound USB 2.0-A, USB 2.0, RS-232C, Ethemet interface (100 Base-TX / 10 Base-T), Wireless LAN a/n (5GHz) (optional), VGA in (2x), VGA out, HDMI in (2x), Composite in, Jack plug out, Jack plug in (2x), Cinch audio out	 Ceiling Mount (White) - ELPMB23 V12H003B23 Ceiling Pipe (450mm) - ELPFP13 V12H003P13 Ceiling Pipe (700mm) - ELPFP14
Epson iProjection App	Ad-Hoc / Infrastructure	V12H003P14
ADVANCED FEATURES		 Adapter - ELPAP11 Wireless LAN (5GHz) V12H005A01
Security	Kensington lock, Control panel lock, Security cable hole, Wireless LAN unit lock, Password protection	 Active Speakers (2 x 15W) - ELPSP02 V12H467040
Other features	AV Mute Slide, Automatic keystone correction, Built-in speaker, Direct Power on/off, Document Camera Compatible, Easy OSD pre-setting, Horizontal and vertical keystone correction, Network projection, OSD copy function, PC Free, Quick Corner, Split-Screen- Function, Wireless LAN capable, iProjecton set-up by QR code	Safety Wire - ELPWR01 V12H003W01
Video Color Modes	Blackboard, Cinema, Dynamic, Sports, sRGB	
GENERAL Power consumption	327 Watt, 225 Watt (economy), 0,3 Watt (standby), On mode power consumption as defined in	
·	JBMS-84 286 Watt	
Product dimensions	309 x 282 x 90 mm (Width x Depth x Height)	
Product weight Noise Level	3,1 kg Normal: 37 dB (A) - Economy: 28 dB (A)	
Included Software Loudspeaker	EasyMP Multi PC Projection, Epson Projector Management 16 Watt	
OTHER		
Warranty	60 months Carry in, Lamp: 60 months or 1.000 h	

EB-982W

LOGISTICS INFORMATION

ѕки	V11H987040
EAN code	8715946680774
Country of Origin	Philippines

1. Requires iProjection App and an internet connection – only compatible with iOS and Android devices, and file sharing limitations may apply.

