

EB-L1715S

DATASHEET / BROCHURE



Versatile 15,000-lumen 3LCD laser projector, offering outstanding fit and forget reliability as well as sharp, vivid imagery with SXGA+ resolution.

Exceptionally bright 15,000-lumen SXGA+ performance combines with rich, vivid colours to make the EB-L1715S installation laser projector an ideal option for large rooms and venues. As well as reliable fit and forget performance, it offers very flexible installation, creating a dedicated solution for scenarios where only maximum performance and durability will do.

Laser-sharp images

Ensure that your presentations, images and video pack a punch with the vivid, sharp projection offered by this 3LCD laser projector. Designed for larger venues, its high resolution SXGA+ images are vivid and bright, even in daylight, while inorganic phosphor wheel technology provides superior light and heat resistance to deliver excellent reliability that lasts for up to 83,000 hours¹.

Flexible positioning

Thanks to a wide range of motorised lenses, including optional ultra-short-throw (UST) lens, the projector benefits from true 360° installation flexibility, allowing it to be placed virtually anywhere - without loss of brightness or distortion of image. The projector also has a built-in camera to ensure accurate calibration and capture diagnostic images (this can be fully disabled to prevent remote access).

Versatile new software

All models in the EB-L1000 series can take advantage of free Epson Professional Projector Tool software from December 2017. It allows you to set up multi-projector installations straight out of the box, simply and quickly, as well as utilising advanced techniques such as projection-mapping and edge-blending.

Quick set-up

Get started quickly thanks to a lens memory function which stores projector settings such as image position, focus and zoom, for prompt access when projecting images in different aspect ratios, or using different lenses.

KEY FEATURES

- **Laser light source technology**
Outstanding brightness and colour, with fit and forget reliability
- **Sharp, clear imagery**
Outstanding clarity and detail for crisp images and readable text
- **Versatile new software**
Set up multiple projector installations and utilise advanced projection techniques
- **Flexible 360° installation**
True flexibility without distortion or loss of brightness
- **Added peace of mind**
Product comes with five-year, 20,000-hour warranty



EPSON
EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System	3LCD Technology
LCD Panel	1,06 inch with C2 Fine

IMAGE

Color Light Output	15.000 Lumen- 10.500 Lumen (economy) In accordance with IDMS15.4
White Light Output	15.000 Lumen - 10.500 Lumen (economy) In accordance with ISO 21118:2020
Portrait Colour Light Output	15.000 lm
Portrait White Light Output	15.000 lm
Resolution	SXGA+ (14000 x 1050), 4:3
Aspect Ratio	4:3
Contrast Ratio	2.500.000 : 1
Native Contrast	2.000 : 1
Light source	Laser
Laser Light source	20.000 hours Durability High, 30.000 hours Durability Eco
Keystone Correction	Manual vertical: ± 45 °, Manual horizontal ± 30 °
Colour Reproduction	Upto 1.07 billion colours

OPTICAL

Throw Ratio	1,62 - 2,65:1
Zoom	Motorized, Factor: 1 - 1,6
Projection Lens Zoom Ratio	1,62 - 2,56 : 1
Lens	Optical
Lens Shift	Motorized - Vertical ± 55 %, horizontal ± 19 %
Lens position memory	10 positions
Screen Size	60 inches - 500 inches
Projection Distance Wide	1,9 m - 16,7 m
Projection Distance Tele	3,2 m - 27,1 m
Projection Distance Wide/Tele	1,93 m - 27,1 m
Projection Lens F Number	1,8 - 2,3
Projection Lens Focal Length	36 mm - 57,35 mm
Projection Lens Focus	Motorized
Interchangeable Lens	Yes

CONNECTIVITY

Interfaces	Jack plug in (3x), Jack plug out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), Wireless LAN b/g/g 25GHz (optional)
Epson iProjection App	Ad-Hoc / Infrastructure

ADVANCED FEATURES

Security	Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection
Other features	Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory
Video Color Modes	Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709
Projector control	via: AMX, Crestron, Extron

GENERAL

Power consumption	1.024 Watt, 647 Watt (economy), 0,3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	586 x 492 x 211 mm (Width x Depth x Height)
Product weight	24 kg
Noise Level	Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF)
Supported Temperature	Storage -10° C - 60° C
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%
Included Software	EasyMP Monitor, EasyMP Multi PC Projection
Options	HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit
Room Type / Application	Meeting room / Classroom, Projection Mapping, Rental / Staging, Visitor Attraction
Positioning	Ceiling Mounted
Colour	Black

OTHER

Warranty	60 months Carry in or 20.000 h
----------	--------------------------------

EB-L1715S

WHAT'S IN THE BOX

- Remote control incl. batteries
- Quick Start Guide
- Power and signal cable (3 m)
- Computer cable
- Cable cover
- CD Manual

OPTIONAL ACCESSORIES

EB-L1715S

- Air Filter - ELP AF51
V13H134A51
- Wireless LAN Adapter - ELP AP10
V12H731P01
- Stacking Frame - ELP MB59 - EB-PU2200 Series (EVO)
V12H996B59
- Ceiling Mount - ELP MB68
V12H006AE0
- Extension Pole - ELP MB70 - For ELP MB68
V12H006AG0
- Truss Adaptor - ELP MB71 - For ELP MB68
V12H006AH0

OPTIONAL LENSES

- Lens - ELPLU03S - Short throw off axis 1 - EB-PU Series
V12H004UA3
- Lens - ELPLL08 - Long throw - EB-PU Series
V12H004L08
- Lens - ELPLM10 - Mid throw 3 - EB-PU Series
V12H004MOA
- Lens - ELPLM11 - Mid throw 4 - EB-PU Series
V12H004MOB
- Lens - ELPLM15 - Mid throw - EB-PU Series
V12H004MOF
- Lens - ELPLU04 - Short throw off axis 2 - EB-PU Series
V12H004U04
- Lens - ELPLW05 - Wide zoom 1 - EB-PU Series
V12H004W05
- Lens - ELPLW06 - Wide zoom 2 - EB-PU Series
V12H004W06
- Lens - ELPLX02 - UST Lens L1500/1700 Series
V12H004X02
- Lens - ELPLW08 - Wide throw - EB-PU2000 Series
V12H004W08

LOGISTICS INFORMATION

SKU	V11H890140
EAN code	8715946645988
Country of Origin	China
Layer	1 Units

1. - Laser life of up to 83,000 hours in custom mode.

EPSON[®]