EB-PU2010W



The EB-PU2010W is a compact and versatile high brightness projector with optional interchangeable lenses and advanced installation features.

This highly versatile 10,000 lumens installation projector is sold as 'body only' and pairs seamlessly with Epson's existing lens family to deliver bright, true-to-life images in a wide variety of environments: from visitor attractions to lecture theatres, museums to meeting rooms. The high lumens EB-PU2010W offers WUXGA resolution with 4K enhancement, HDR and advanced installation features.

Superior image quality

The 10,000 lumens EB-PU2010W projects clear whites, vivid details, deep blacks, defined shadows and high contrast imagery.

Compact and lightweight

The compact size makes this projector more transportable and saves storage space, providing size and cost advantages to projector fleets. The unobtrusive design allows it to blend seamlessly into most environments. Also available in black.

Interchangeable lens support

The EB-PU2010W accommodates different lenses to suit a wide range of projection environments, including a zero-offset ultra-short-throw lens. Epson supplies the projector as 'body only', without a lens, which puts the power to build the right projection solution, for the right application, in the hands of the user.

Designed for installation agility

Produce large-scale, extremely bright displays, even as part of multi-projector installations where edge blending, stacking and lens flexibility is key. Epson Projector Professional Tool makes advanced installation techniques easy, such as projection mapping, while the optional external camera module (ELPEC01) uses built-in processing for PC-free geometry correction for stacking. The EB-PU2010W features NFC for multi-projector set up, making diagnostics and installations easier using the Epson Projector Config Tool. Also includes SDI input and output connectivity.

DATASHEET / BROCHURE

































- Compact and lightweight
 Unobtrusive and easier to transport
- Lens support
 Supports a wide selection of Epson interchangeable lenses
- Enhanced design
 Clean, simple, and discreet design.
- Image quality 10,000 lumens, 3LCD, WUXGA resolution with 4K enhancement
- Advanced installation tools
 A range of free software tools and an optional external camera module





PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology, RGB liquid crystal shutter

LCD Panel 1,03 inch with C2 Fine

IMAGE

Color Light Output 10.000 Lumen - 7.000 Lumen (economy) In accordance with IDMS15.4

White Light Output 10.000 Lumen - 7.000 Lumen (economy) In accordance with ISO 21118:2020

 Portrait Colour Light Output
 10.000 Im

 Portrait White Light Output
 10.000 Im

 Resolution
 WUXGA

 High Definition
 4K enhancement

Aspect Ratio 16:10

Contrast Ratio Over 2.500.000 : 1
Native Contrast 2.000 : 1

Light source Laser

Laser Light source 20.000 hours Durability High, 30.000 hours Durability Eco

Keystone Correction Manual vertical: \pm 45 °, Manual horizontal \pm 30 °

Colour Video Processing 10 Bits

Colour Reproduction Upto 1.07 billion colours

HDR support HDR10, HLG

OPTICAL

Throw Ratio 0,35 - 7,41:1 Motorized Zoom Lens Optical Lens Shift varies by lens Screen Size varies by lens Projection Distance Wide)varies by lens Projection Distance Tele)varies by lens Projection Distance Wide/Tele) varies by lens Projection Lens F Number varies by lens Projection Lens Focal Length varies by lens Projection Lens Focus Motorized Offset varies by lens Interchangeable Lens Yes Standard Lens Not included

CONNECTIVITY

Interfaces USB 2.0-A (2x), USB 2.0 Type B (Service Only), RS-232C, Ethernet interface (100 Base-TX / 10

Base-T), Wireless LAN IEEE 802.11a/b/g/n (optional), VGA in, DVI in, HDBaseT, Jack plug out, HDMI (HDCP 2.3), 3G-SDI Input, 3G-SDI Output, Near Field Communication (NFC), USB

content playback, Remote

Network Protocol HTTPS, IPv6, SNMP, ESC/VP.net, PJLink

ADVANCED FEATURES

Security Kensington lock, Control panel lock, Padlock, Security cable hole, Wireless LAN unit lock,

Wireless LAN security, Password protection

Other features 21:9 aspect ratio support, 4K enhancement, A/V mute, Auto Power On, Auto source search,

Direct Power on/off, Edge Blending, Long light source life, OSD copy function, Point correction, Power on button, Quick Corner, Schedule Function, Super resolution, Web Control,

Web Remote, iProjection App

Video Color Modes Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT709
Projector control via: Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery

EB-PU2010W

WHAT'S IN THE BOX

- Remote control incl. batteries
- Power cable
- Cable cover
- Lens connector cap
- User's Manual Set
- Warranty Documents





PRODUCT SPECIFICATIONS

EB-PU2010W

GENERAL

Power consumption 535 Watt, 452 Watt (economy), 0,5 Watt (standby), On mode power consumption as defined in

JBMS-84 462 Watt

Heat Dissipation 1.819 BTU/hour (max)

Supply Voltage AC 100 V - 240 V, 50 Hz - 60 Hz

Product dimensions 545 x 436 x 189 mm (Width x Depth x Height)

Product weight 16,8 kg

Noise Level Normal: 37 dB (A) - Economy: 30 dB (A)

Supported Temperature Storage -10° C - 60° C

Supported Humidity Operation 20% - 80%, Storage 10% - 90%

If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could

break and cause the projector to drop from the ceiling.

If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional

assistance

Included Software Epson Creative Projection, EasyMP Multi PC Projection, Epson Projector Config Tool, Epson

Projector Content Manager, Epson Projector Management, Epson Projector Professional Tool

ptions Camera module, Ceiling mount, Wireless LAN unit

Room Type / Application Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection

Mapping, Rental / Staging, Signage / Retail, Visitor Attraction

Positioning Ceiling Mounted, Desktop, Flying Frame

Colour White

OTHER

Warranty 36 months Carry in



OPTIONAL ACCESSORIES

EB-PU2010W

- Adapter ELPAP11 Wireless LAN (5GHz)
- V12H005A01
- Air Filter ELPAF46
- V13H134A46
- Camera Unit ELPEC01
- V12HA46010
- External Air Filter ELPAF63 EB-PU1000 Series
 - V13H134AD0
- Ceiling Mount ELPMB68
 - V12H006AE0
- Portrait Adaptor ELPMB69 For ELPMB68
- V12H006AF0
- Extension Pole ELPMB70 For ELPMB68
- V12H006AG0
- Truss Adaptor ELPMB71 For ELPMB68

V12H006AH0

OPTIONAL LENSES

- Lens ELPLL08 Long throw EB-PU Series V12H004L08
- Lens ELPLM10 Mid throw 3 EB-PU Series V12H004M0A
- Lens ELPLM11 Mid throw 4 EB-PU Series V12H004M0B
- Lens ELPLM15 Mid throw EB-PU Series V12H004M0F
- Lens ELPLU03S Short throw off axis 1 EB-PU Series
- Lens ELPLU04 Short throw off axis 2 EB-PU Series V12H004U04
- Lens ELPLW05 Wide zoom 1 EB-PU Series V12H004W05
- Lens ELPLW06 Wide zoom 2 EB-PU Series V12H004W06
- Lens ELPLW08 Wide throw EB-PU2000 Series V12H004W08
- Lens ELPLX02WS UST EB-PU2000 Series V12H004Y0B

LOGISTICS INFORMATION

sкu	V11HA52940
EAN code	8715946697451
Country of Origin	Philippines



