



A moulded connector on one end, and a male phoenix connector on the other end which can be plugged directly into the rear of module.

3m (9.8ft) END OF LIFE OCTOBER 2020

TC2 3MVGA EU SAP: 3000667 US SAP: 12939523

5m (16.4ft)

TC2 5MVGA EU SAP: 2042118 US SAP: 12939527

10m (32.8ft)

TC2 10MVGA EU SAP: 1461166 US SAP: 12939464

15m (49.2ft) END OF LIFE

TC2 15MVGA EU SAP: 1461168 US SAP: 12939467

20m (65.6ft) END OF LIFE

TC2 20MVGA EU SAP: 1461174 US SAP: 12939469

SPECIFICATIONS

TC2 3MVGA White VGA to Phoenix Cable 3m (9.8ft)

SHEATH PVC, OUTER DIAMETER

8.0 mm (0.31")

CONDUCTOR THICKNESS

28AWG

COVERAGE BRAIDED SHIELD

>65%

IMPEDANCE

at 10MHz, 75Ω (coaxial cable)

RESISTANCE 20°C(Ω/1000M)

237.25

PACKAGED DIMENSIONS

180 x 180 x 70 mm (7.1" x 7.1" x 2.8")

FERRITE CORE TO STOP RF INTERFERENCE

DRAIN WIRE LAID BETWEEN ALUMINUM BRAID

NICKEL-PLATED CONNECTORS

AL-MG ALLOY WIRE OVERALL

TC2 5MVGA White VGA to Phoenix Cable 5m (16.4ft)

SHEATH PVC, OUTER DIAMETER

8.0 mm

CONDUCTOR THICKNESS

28AWG

COVERAGE BRAIDED SHIELD

>65%

IMPEDANCE

10MHz, 75Ω (coaxial cable)

RESISTANCE 20°C(Ω/1000M)

237.25

PACKAGED DIMENSIONS

180 x 180 x 70 mm (7.1" x 7.1" x 2.8")

FERRITE CORE TO STOP RF INTERFERENCE**DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****NICKEL-PLATED CONNECTORS****AL-MG ALLOY WIRE OVERALL**

TC2 10MVGA White VGA to Phoenix Cable 10m (32.8ft)

SHEATH PVC, OUTER DIAMETER

8.0 mm

CONDUCTOR THICKNESS

28AWG

COVERAGE BRAIDED SHIELD

>65%

IMPEDANCE (COAXIAL CABLE)

10MHz, 75Ω

RESISTANCE 20°C(Ω/1000M)

237.25

PACKAGED DIMENSIONS

200 x 200 x 90 mm (7.87" x 7.87" x 3.54")

FERRITE CORE TO STOP RF INTERFERENCE**DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****NICKEL-PLATED CONNECTORS****AL-MG ALLOY WIRE OVERALL**

TC2 15MVGA White VGA to Phoenix Cable 15m (49.2ft)

SHEATH PVC, OUTER DIAMETER

8.0 mm

CONDUCTOR THICKNESS

28AWG

COVERAGE BRAIDED SHIELD

>65%

IMPEDANCE (COAXIAL CABLE)

10MHz, 75Ω

RESISTANCE 20°C(Ω/1000M)

237.25

PACKAGED DIMENSIONS

200 x 200 x 90 mm (7.87" x 7.87" x 3.54")

FERRITE CORE TO STOP RF INTERFERENCE**DRAIN WIRE LAID BETWEEN ALUMINUM BRAID****NICKEL-PLATED CONNECTORS****AL-MG ALLOY WIRE OVERALL**

TC2 20MVGA White VGA to Phoenix Cable 20m (65.6ft)

OUTER DIAMETER

8.0 mm

CONDUCTOR THICKNESS

28AWG

IMPEDANCE

10MHz

RESISTANCE

20°C(Q/1000m) 237.25

COAXIAL CABLE

75Ω

PACKAGED DIMENSIONS

250 x 250 x 100 mm (9.84" x 9.84" x 3.94")